



Digital Signage Box

BM-8112



Features:

- Playlist & Schedule Control
- S-video & Composite & YPbPr output interface
- Supports internal IDE hard disk
- Support USB & CF-II flash memory
- Support music and photo slideshow

Specifications:

Digital Media Processor

High performance audio / photo / video engine
HD component output for 720P JPEG display
Scaler for video up-conversion to 720P
Pixel adaptive de-interlacer
2 channel stereo audio DAC
Support music and photo slideshow application

Storage Device Interface

USB 2.0 host port x 1
USB 1.1 host port x 1
1 Compact Flash II socket for CF-II card
1 IDE 44-pin connector for IDE hard disk

Enhanced Operation Control

Playlist & Schedule Control

Video Output Port

S-Video connector
Composite connector
YPbPr connector

Audio Output Port

Phone jack stereo output connector
Support audio amplifier and volume control

Input DC Power

12V

IR Remote Control

Multi-button control for operation of media player

Playable Format Support

Content / Card	Minimum	Maximum	CF	USB flash	HDD
JPEG, TIFF, BMP	16x16	5120x3840	YES	YES	YES
MP3	32K bps	256K bps	YES	YES	YES
MPEG1			YES	YES	YES
MPEG4 SP		QVGA/CIF	YES	YES	YES
MPEG4 ASP		D1	YES	YES	YES
Divx 3.x/4.x/5.x		D1	YES	YES	YES
MPEG2		D1	NO	YES	YES

Case Dimension

Case Dimension: 230 (L) mm x 130 (W) mm x 40 (H) mm
Weight: 1Kg

Product Application:

- Digital Signage
- Information Terminal

Ordering Information:

- BM-8112 (Audio, S-Video, Composite, YPbPr output)