



Industrial LCD Monitor - Close Frame

LM-X215400 Series



Features:

- Close frame architecture with black cover and bezel
- 15.0" TFT LCD supports 1024 x 768 resolutions
- Wide range of operation temperature: -20°C ~ 70°C
- Wide viewing angle: 80 (H & V)
- High contrast ratio (700 : 1)
- Sturdy & Lightweight aluminum chassis
- High performance Genesis LCD controller
- Luminance 450 nits
- Standard RGB signal input interface
- Optional support for DVI & Video interface
- Optional support for touch screen

Specifications:

Signal Input Interface

RGB
DVI (Optional)
RCA_Jack, S_Video (Optional)
YCbCr (Optional)

OSD Control

Auto-detection & Auto-adjustment
Horizontal & Vertical position adjustment
Brightness / Contrast / Hue / Saturation adjustment
Auto color setup and adjustment

Resolution & Display Color

Display Color: 16, 194, 277 colors
XGA 1024 x 768 @ 60HZ, 70HZ, 75HZ
SVGA 800 x 600 @ 60HZ, 70HZ, 75HZ
VGA 640 x 480 60HZ, 70HZ, 75HZ

Mechanical Characteristic

Dimension (L x W x H): 364.3mm x 267.3mm x 54.2mm
Weight: TBD
Color: Black and Original aluminum

Power

Power Adapter: 60W
AC Input Voltage: 90VAC to 264VAC
AC Input Frequency: 50/60 HZ
Max. Load Current: 5A

Architecture

Aluminum chassis
Standard VESA mounting holes (75 / 100mm)
Four versatile mounting brackets

Panel Specifications

Item	Specification	Unit	
1	Diagonal Size	15.0	inch
2	Active Area	304.128(H) x 228.096(V)	mm
3	Bezel Opening Area	307.4(H) x 231.3(V)	mm
4	Driver Element	a-si TFT active matrix	-
5	Pixel Number	1024 x R.G.B. x 768	pixel
6	Pixel Pitch	0.297(H) x 0.297(V)	mm
7	Display Color	16, 194, 277	color
8	Center Luminance of White	450	nit
9	Contrast Ratio	700	-
10	Response Time	TR=8, TF=17	ms
11	Viewing Angle	80 (H & V)	degree
12	Backlight MTBF	50,000	hour
13	Panel Type	TFT Active	-
14	Storage Temperature	-20 ~ 80	°C
15	Operation Temperature	-20 ~ 70	°C

Ordering Information:

Model Number	Type	Brightness (nit)	Interface	Touch Screen	Touch Interface
LM-X215400	Close frame	450	RGB	N/A	N/A
LM-X215420	Close frame	450	RGB, DVI	N/A	N/A
LM-X215450	Close frame	450	RGB, DVI, Composite, S_Video	N/A	N/A
LMS-X215401	Close frame	450	RGB	5-Wire R_Touch	USB
LMS-X215421	Close frame	450	RGB, DVI	5-Wire R_Touch	USB
LMS-X215451	Close frame	450	RGB, DVI, Composite, S_Video	5-Wire R_Touch	USB

www.spectrah.com

Spectrah Dynamics, Inc.

Tel: 886-2-86472026 | Fax: 886-2-86472201 | E-mail: spec_info@spectrah.com
Add: 5F-2, No. 188, Sec #3, Ta-tung Road, Hsi-Chi, Taipei Hsien 221, Taiwan.